



Splash guard/pipe stopper in rodding eye if requested by the statutory undertaker

Wall of manhole chamber

Invert of rodding eye to be not greater than 1.5m above top of benching (unless specific man access requirements are provided)

- Notes:
- 1.- All dimensions are nominal and in millimetres
 - 2.- All temporary and enabling works by constructor
 - 3.- This document is intended for guidance only
 - 4.- Additional rocker pipes may be necessary to accommodate transition of pipe gradient to vertical downpipe
 - 5.- Seals are required to enable an air-tight system
 - 6.- This document is uncontrolled and updates will not be issued automatically

This information is for guidance purposes only. Please note that we may change the information from time to time, for a variety of reasons. This information cannot be relied upon to determine the suitability or installation requirements of our products for your particular site conditions or application; expert advice is required in this respect. Final determination of the suitability of any information or material for your intended use and manner of use is your sole responsibility and you must assume all risk and liability in this regard. This information is not intended to have any legal effect, whether by way of advice, representation or warranty. However, our technical staff will be happy to discuss your particular application and site conditions in further detail.



Polypipe Civils Ltd.
Civils & Agricultural Products
 UNION WORKS, BISHOP MEADOW ROAD,
 LOUGHBROUGH, LEICESTERSHIRE, LE11 5RE,
 TEL: 01509 615100 FAX: 01509 615205

DRAWING STATUS:	DRAFT FOR APPROVAL
DRAWING TITLE	EXAMPLE OF VERTICAL BACKDROP DETAIL

PROJECT REF:	SCALE
CAD File: 16053D1.DWG	NOT TO SCALE
DRAWING No. 16053D1	REV

DRAWN BY	IDA	DATE	11/10/01
CHECKED			
DIMENSIONS IN MILLIMETRES UNLESS OTHERWISE STATED			